


# RIDEMAX FL 693 M



|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>VF 500/50 R 17</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 156 D  |

## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94069453 | <b>RC (IN)</b> | 113.4           |
| <b>SW (IN)</b>  | 19.8     | <b>RIM REC</b> | 16.00           |
| <b>OD (IN)</b>  | 36.7     | <b>ECE</b>     | E11-106R-007200 |
| <b>SLR (IN)</b> | 16.6     |                |                 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41    | 46    | 52    | 58    | 65    | 73    |
|-----------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45        | 2420 | 3060 | 3700 | 4110 | 4740 | 5380  | 5950  | 6510  | 7150  | 7630  | 8030  |
| 40        | 2650 | 3360 | 4060 | 4500 | 5210 | 5910  | 6530  | 7150  | 7850  | 8380  | 8820  |
| 30        | 3210 | 4060 | 4920 | 5450 | 6310 | 7160  | 7910  | 8660  | 9510  | 10150 | 10670 |
| 25        | 3610 | 4570 | 5530 | 6120 | 7080 | 8040  | 8890  | 9730  | 10690 | 11400 | 12000 |
| 15        | 4190 | 5310 | 6420 | 7110 | 8230 | 9340  | 10320 | 11290 | 12410 | 13240 | 13940 |
| 5         | 4770 | 6050 | 7310 | 8110 | 9370 | 10640 | 11750 | 12870 | 14140 | 15080 | 15880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.