

# EARTHMAX SR 475



**EARTHMAX**  
RADIAL OTR TIRES

# EARTHMAX SR 475

EARTHMAX SR 475 is an all steel radial tyre specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.



|      | SIZE       | TT/TL | TRA CODE | STAR RATING | LI/SS | RIM                                                                               |         | TKPH (TK/H) | OW (MM) (mm)                                                                        | OD (mm)                                                                             | SLR (mm)                                                                            | RC (mm)                                                                             | TREAD DEPTH (MM) | VERSION |
|------|------------|-------|----------|-------------|-------|-----------------------------------------------------------------------------------|---------|-------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------|---------|
|      |            |       |          |             |       | REC RIM                                                                           | ALT RIM |             |                                                                                     |                                                                                     |                                                                                     |                                                                                     |                  |         |
|      |            |       |          |             |       |  |         |             |  |  |  |  |                  |         |
| Ø33" | 18.00 R 33 | TL    | E4       | ***         | 195 B | 13.00/2.5                                                                         | -       | 265         | 490                                                                                 | 1860                                                                                | 860                                                                                 | 5721                                                                                | 50               | CR      |
|      | 18.00 R 33 | TL    | E4       | ***         | 195 B | 13.00/2.5                                                                         | -       | 292         | 490                                                                                 | 1860                                                                                | 860                                                                                 | 5721                                                                                | 50               | STD     |
|      | 18.00 R 33 | TL    | E4       | **          | 191 B | 13.00/2.5                                                                         | -       | 265         | 490                                                                                 | 1860                                                                                | 860                                                                                 | 5721                                                                                | 50               | CR      |
| Ø35" | 24.00 R 35 | TL    | E4       | **          | 209 B | 17.00/3.5                                                                         | -       | 422         | 654                                                                                 | 2160                                                                                | 971                                                                                 | 6589                                                                                | 59               | STD     |

CR: CUT RESISTANT COMPOUND, STD: STANDARD

| TECHNOLOGIES                                                                        |                                                                                     |                                                                                     | PERFORMANCES                                                                        |                                                                                       |                                                                                       |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |  |
|  |  |                                                                                     |                                                                                     |                                                                                       |                                                                                       |                                                                                       |                                                                                       |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

| SIZE       | TT/TL | TRA<br>CODE | STAR<br>RATING | LI/SS | RIM                                                                               |         | TKPH<br>(TK/H) | OW<br>(MM)                                                                         | OD                                                                                  | SLR                                                                                 | RC                                                                                  | TREAD<br>DEPTH<br>(MM) | VERSION |
|------------|-------|-------------|----------------|-------|-----------------------------------------------------------------------------------|---------|----------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------|---------|
|            |       |             |                |       | REC RIM                                                                           | ALT RIM |                | (mm)                                                                               | (mm)                                                                                | (mm)                                                                                | (mm)                                                                                |                        |         |
|            |       |             |                |       |  |         |                |  |  |  |  |                        |         |
| 24.00 R 35 | TL    | E4          | **             | 209 B | 17.00/3.5                                                                         | -       | 355            | 654                                                                                | 2160                                                                                | 971                                                                                 | 6589                                                                                | 59                     | CR      |

CR: CUT RESISTANT COMPOUND, STD: STANDARD



| TECHNOLOGIES                                                                        |                                                                                     |                                                                                     | PERFORMANCES                                                                        |                                                                                       |                                                                                       |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026