


AGRIMAX V-FLECTO

TIRE SIZE	VF 540/65 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	154 D



DIMENSIONS IS STANDARD

SW (MM)	549	RIM REC	DW 20 B
OD (MM)	1413	RIM ALT	DW 18 L
SLR (MM)	622	ECE	E11-106R-005710
RC (MM)	4160	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	1910	2250	2555	2865	3135	3410
FROM 65 TO 40	2100	2475	2810	3150	3450	3750
30	2140	2520	2865	3210	3515	3825
20	2180	2570	2920	3275	3585	3900
10	2310	2720	3090	3465	3795	4125
*UPTO 10 CYC WITH FRONT LOADER	2940	3465	3930	4410	4830	5250
10 HT	2140	2520	2865	3210	3515	3825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.