

# AGRIMAX V- FLECTO

**VF 480/80 R 50**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STEEL BELTED SPL
<b>TIRE TYPE</b>	TL



## UNDEFINED US STANDARD

<b>USA CODE</b>	94512225	<b>RC (IN)</b>	243.9
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW16L
<b>OD (IN)</b>	80.2	<b>RIM ALT</b>	DW15L
<b>SLR (IN)</b>	36.9	<b>ECE</b>	E11-106R-0010595

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
45	5750	6690	7620	8710	9640	10570	11660	12280	13520	14620	15540
<b>FROM 40 TO 25</b>	6330	7350	8380	9570	10590	11620	12820	13500	14870	16060	17080
20	6450	7500	8540	9770	10810	11860	13070	13770	15170	16390	17430
12	6580	7650	8710	9950	11020	12090	13330	14040	15460	16710	17770
5	6960	8090	9210	10530	11660	12790	14100	14850	16360	17670	18790
<b>UPTO 20 CYCLIC</b>	7180	8340	9500	10870	12030	13190	14550	15320	16880	18230	19390
<b>UPTO 10 CYCLIC</b>	8560	9950	11340	12960	14350	15740	17360	18290	20140	21760	23150
<b>UPTO 5 CYCLIC</b>	9390	10910	12430	14210	15730	17250	19020	20040	22070	23840	25360
5 HT	6450	7500	8540	9770	10810	11860	13070	13770	15170	16390	17430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.