


# AGRIMAX V-FLECTO

**VF 520/85 R 50**

**UM** US STANDARD

**CONSTRUCTION**  RADIAL

**VERSION** STEEL BELTED

**TIRE TYPE** TL

177 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94517008	<b>RC (IN)</b>	255.6
<b>SW (IN)</b>	21.1	<b>RIM REC</b>	DW 18 L
<b>OD (IN)</b>	85.0	<b>RIM ALT</b>	DW 16 L
<b>SLR (IN)</b>	38.3	<b>ECE</b>	E11-106R-0011305

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6880	7900	9070	10240	11410	12590	13760	14640
<b>FROM 40 TO 25</b>	7560	8690	9980	11260	12540	13830	15120	16090
20	7700	8860	10170	11490	12800	14110	15420	16410
12	7860	9030	10370	11710	13050	14380	15720	16730
5	8310	9560	10970	12390	13800	15220	16630	17700
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	10590	12170	13980	15770	17580	19380	21190	22530
5HT	7700	8860	10170	11490	12800	14110	15420	16410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.