

# AT 171

<b>TIRE SIZE</b>	<b>40X9 - 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	90 A8 ; 66 F



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	211	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	995	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	462	<b>PR</b>	8
<b>RC (MM)</b>	3112	<b>TRA CODE</b>	R1W+

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.40	1.00
40 MUD BOGGING	600	-
80 MUD BOGGING	300	-
40 CASUAL TRANSPORT	-	485
80 CASUAL TRANSPORT	-	243

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.