


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 800/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	187 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94073979	<b>RC (IN)</b>	242.3
<b>SW (IN)</b>	31.7	<b>RIM REC</b>	DW 28 B
<b>OD (IN)</b>	82.1	<b>RIM ALT</b>	DW25 B; DW27B; DW30B
<b>SLR (IN)</b>	35.0	<b>ECE</b>	E11-106R-007205

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9790	11350	12920	14680	16250	17810	19560
<b>FROM 40 TO 25</b>	10750	12470	14190	16130	17850	19560	21490
20	10970	12720	14470	16450	18200	19950	21920
12	11180	12970	14760	16770	18560	20350	22350
5	11830	13720	15610	17740	19630	21520	23640
<b>UPTO 20 CYC</b>	12200	14150	16100	18310	20260	22210	24400
<b>UPTO 10 CYC</b>	14570	16900	19220	21850	24180	26510	29130
<b>UPTO 5 CYC</b>	15960	18520	21080	23940	26500	29060	31920
5 HT	10970	12720	14470	16450	18200	19950	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.