

FARM 2000

| | |
|--------------------|---------------|
| TIRE SIZE | 250/80 - 18 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 115 A8 |
| LI/SS FREE ROLLING | 127 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 240 | RIM REC | W 8 |
| OD (MM) | 870 | RIM ALT | W7; W9 |
| SLR (MM) | 394 | ECE | E11-106R-003519 |
| RC (MM) | 2679 | SRI | 410 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|------------|------|
| 10 FR | 2450 |
| 25 FR | 2085 |
| 30 FR | 1960 |
| 40 FR | 1750 |
| 10 DW | 1700 |
| 25 DW | 1445 |
| 30 DW | 1360 |
| 40 DW | 1215 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.