


# AGRIMAX SPARGO

VF 380/90 R 50

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	175 D



## UNDEFINED IS STANDARD

SW (MM)	390	RIM REC	W13 B
OD (MM)	1950	RIM ALT	W12 B
SLR (MM)	893	ECE	E11-106R-006400
RC (MM)	5950	SRI	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	3010	3385	3700	3890	4075	4200	4325	4580	4765	4955	5145	5330	5455	5645	5770	6020	6275
FROM 65 TO 40	3310	3725	4070	4275	4485	4620	4760	5035	5240	5450	5655	5865	6000	6210	6345	6620	6900
30	3375	3795	4150	4360	4570	4710	4850	5135	5345	5555	5765	5975	6120	6330	6470	6750	7035
20	3440	3870	4230	4445	4660	4805	4950	5235	5450	5665	5880	6095	6240	6455	6600	6885	7175
10	3640	4095	4475	4705	4930	5085	5235	5540	5765	5995	6220	6450	6600	6830	6980	7285	7590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.