


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/60 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIONI IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1745	RIM ALT	DW 21 B
SLR (MM)	774	ECE	E11-106R-005712
RC (MM)	5231	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2650	3080	3515	3950	4385	4820
FROM 65 TO 40	2915	3390	3865	4345	4820	5300
30	2970	3455	3940	4430	4915	5405
20	3030	3525	4015	4515	5010	5510
10	3205	3725	4250	4775	5300	5830
*UPTO 10 CYC WITH FRONT LOADER	4080	4745	5410	6080	6745	7420
10HT	2970	3455	3940	4430	4915	5405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.