

# AGRIMAX RT 855

	<b>210/90 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	110 A8/B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	211	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	890	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	412	<b>ECE</b>	E4-106R-001817
<b>RC (MM)</b>	2681	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	500	575	660	745	830	915	990	1060
40	500	575	660	745	830	915	990	1060
30	535	615	705	795	890	980	1060	1135
10 LT	670	770	885	1000	1115	1230	1330	1425
10 HT	535	615	705	795	890	980	1060	1135

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.