


AGRIMAX TERIS

900/60 R 32 CHO

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ
VERSION	STANDARD
TIRE TYPE	TL
	185 A8 ; 182 B



UNDEFINED IS STANDARD

SW (MM)	875	RIM REC	DW 27 B
OD (MM)	1910	RIM ALT	DW 28 B ; DW 30 B
SLR (MM)	875	ECE	E4-106R-001433
RC (MM)	5775	SRI	900

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	3375	3825	4800	5325	5925	6375	6975	7500	7990	8500
40	3715	4210	5280	5860	6520	7015	7675	8250	8695	9250
30	3975	4505	5655	6270	6980	7510	8215	8830	9305	9900
15 CYC	6130	6945	8715	9670	10760	11575	12665	13615	14350	15265
10 CYC	6685	7575	9505	10545	11735	12625	13815	14850	15655	16650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.