


RIDEMAX FL 615

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | VF 800/65 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAILER / TANKER / SPREADER / IMPLEMENTS |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 190 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 815 | RIM REC | DW 28 B |
| OD (MM) | 1850 | RIM ALT | DW 27 B |
| SLR (MM) | 811 | ECE | E11-106R-0010408 |
| RC (MM) | 5610 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------|------|------|-------|-------|-------|-------|
| 65 | 5195 | 5830 | 7105 | 8060 | 9330 | 10600 |
| 50 | 6080 | 6825 | 8315 | 9430 | 10920 | 12405 |
| 40 | 6705 | 7525 | 9165 | 10395 | 12035 | 13675 |
| 30 | 7330 | 8225 | 10020 | 11365 | 13160 | 14950 |
| 25 | 7590 | 8515 | 10375 | 11765 | 13625 | 15480 |
| 20 | 7900 | 8865 | 10800 | 12250 | 14185 | 16115 |
| 10 | 8520 | 9565 | 11650 | 13215 | 15300 | 17385 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.