


AGRIMAX FORCE

TIRE SIZE	IF 800/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	184 D



РАЗМЕРЫ IS STANDARD

SW (MM)	794	RIM REC	DW 27 B
OD (MM)	2085	RIM ALT	DW 25 B; DW 28 B; DW 30 B
SLR (MM)	923	ECE	E11-106R-006497
RC (MM)	6184	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3845	4500	5155	5730	6305	6795	7615	8190
FROM 65 TO 40	4230	4950	5670	6300	6930	7470	8370	9000
30	4395	5145	5895	6550	7205	7765	8700	9360
20	4565	5345	6120	6800	7480	8065	9035	9720
10	5370	6285	7200	8000	8800	9485	10625	11430
UPTO 30 CYC	5495	6435	7370	8190	9005	9710	10880	11700
UPTO 15 CYC	6555	7670	8785	9765	10740	11575	12970	13950
UPTO 10 CYC	7190	8415	9635	10710	11780	12695	14225	15300
10 HT	4395	5145	5895	6550	7205	7765	8700	9360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.