

# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>400/70 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	152 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	404	<b>RIM REC</b>	13
<b>OD (MM)</b>	1170	<b>RIM ALT</b>	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L
<b>SLR (MM)</b>	542	<b>ECE</b>	E11-106R-003958
<b>RC (MM)</b>	3597	<b>SRI</b>	575

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1705	2025	2310	2630	2950	3160	3550	-	-
40	1705	2025	2310	2630	2950	3160	3550	-	-
30	1825	2170	2470	2815	3155	3385	3800	-	-
25	1895	2250	2565	2920	3275	3515	3945	-	-
10 CYC.	2080	2560	3010	3465	3945	4290	4850	5115	5325
STATIC	3185	3920	4615	5310	6045	6575	7435	7840	8165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.