

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	143 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94039593	<b>RC (IN)</b>	180.3
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	59.4	<b>RIM ALT</b>	W 9; W 10; DW 10; DW11
<b>SLR (IN)</b>	27.6	<b>ECE</b>	E4-106R-000781

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
<b>30</b>	2170	2520	3310	4030	4390	4700	5110	5530	6000
<b>25</b>	2170	2520	3310	4030	4390	4700	5110	5530	6000
<b>20</b>	2330	2710	3550	4320	4710	5030	5480	5930	6440
<b>5 LT</b>	2910	3390	4440	5400	5890	6290	6860	7420	8060
<b>5 HT</b>	2330	2710	3550	4320	4710	5030	5480	5930	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.