


# FL 635

<b>TIRE SIZE</b>	<b>500/45 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	136 D



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94075607	<b>RC (IN)</b>	121.5
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	40.2	<b>ECE</b>	E11-106R-0010082
<b>SLR (IN)</b>	18.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41
45	2480	3020	3430	3970	4500
40	2720	3320	3760	4350	4940
30	3300	4010	4550	5270	5990
25	3700	4510	5110	5920	6720
20	4110	5000	5680	6570	7460
15	4300	5240	5940	6880	7800
5	4890	5960	6770	7840	8900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.