

EARTHMAX SR 35



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 35

EARTHMAX SR 35 is a low-profile All Steel radial tyre specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. EARTHMAX SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tyre is available as cut-resistant compound for a maximum service life even under severe conditions.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	750/65 R 25 (30/65 R 25)	TL	E3	**	190 B	24.00/3.0	22.00/3.0 25.00/3.0	223	740	1601	715	4802	42	CR
	750/65 R 25 (30/65 R 25)	TL	E3/L3	**/*	190 B 202 A2	24.00/3.0	22.00/3.0 25.00/3.0	223	740	1601	715	4802	42	CR
	750/65 R 25 (30/65 R 25)	TL	L3	**	209 A2	24.00/3.0	22.00/3.0 25.00/3.0	0	740	1601	715	4802	42	CR
	650/65 R 25 (25/65 R 25)	TL	E3	**	180 B	19.50/2.5	-	202	635	1498	669	4493	39	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES			
						
						

Permissible tolerances: O.D. 2%–5.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	650/65 R 25 (25/65 R 25)	TL	L3	*	193 A2	19.50/2.5	-	0	635	1498	669	4493	39	CR
	650/65 R 25 (25/65 R 25)	TL	E3/L3	**/*	180 B 193 A2	19.50/2.5	-	202	635	1498	669	4493	39	CR
Ø29"	775/65 R 29	TL	L3	**	213 A2	24.00/3.5	24.00/3.0 25.00/3.5	0	775	1752	787	5311	45	CR
	875/65 R 29 (35/65 R 29)	TL	E3/L3	**/*	203 B 214 A2	27.00/3.50	27.00/3.0 28.00/3.5	279	890	1860	816	5559	48	CR
	775/65 R 29	TL	E3/L3	**/*	195 B 206 A2	24.00/3.5	24.00/3.0 25.00/3.5	220	775	1752	787	5311	45	CR
	875/65 R 29 (35/65 R 29)	TL	E3	**	203 B	27.00/3.50	27.00/3.0 28.00/3.5	279	890	1860	816	5559	48	CR
	875/65 R 29 (35/65 R 29)	TL	L3	*	214 A2	27.00/3.50	27.00/3.0 28.00/3.5	0	890	1860	816	5559	48	CR
	775/65 R 29	TL	E3	**	195 B	24.00/3.5	24.00/3.0 25.00/3.5	220	775	1752	787	5311	45	CR
	775/65 R 29	TL	L3	*	206 A2	24.00/3.5	24.00/3.0 25.00/3.5	0	775	1752	787	5311	45	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES		
					
E3/L3	B	214 kg			

Permissible tolerances: O.D. 2%–5.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES	
	 E3/L3		   
	 214 kg		

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026