


AGRIMAX RT 945

| | |
|---------------------|--|
| TIRE SIZE | 380/90 R 54 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 158 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 380 | RIM REC | W 12 |
| OD (MM) | 2056 | RIM ALT | W 11; W 13 |
| SLR (MM) | 962 | ECE | E4-106R-001488 |
| RC (MM) | 6232 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 1955 | 2510 | 3060 | 3315 | 3615 | 3955 | 4250 | - |
| 40 | 1955 | 2510 | 3060 | 3315 | 3615 | 3955 | 4250 | - |
| 30 | 2095 | 2685 | 3280 | 3550 | 3870 | 4235 | 4550 | - |
| 10 | 2295 | 3000 | 3635 | 4335 | 4975 | 5165 | 5740 | 6375 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.