

# FL 630 SUPER

<b>TIRE SIZE</b>	<b>650/65 R 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94045587	<b>RC (IN)</b>	183.2
<b>SW (IN)</b>	25.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	59.8	<b>ECE</b>	E4-106R-001651
<b>SLR (IN)</b>	26.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	4310	4980	5650	6870	7940	9150	10360	11170	12380	13450
40	4730	5470	6210	7540	8720	10050	11380	12270	13590	14770
30	5730	6620	7520	9130	10550	12160	13770	14850	16460	17880
25	6440	7440	8440	10250	11860	13670	15480	16690	18500	20090
15	7470	8640	9810	11920	13780	15880	17980	19380	21480	23350
5	8510	9840	11180	13570	15700	18090	20480	22070	24470	26590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.