


AGRIMAX V-FLECTO

TIRE SIZE	VF 750/70 R 44
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	186 D



DIMENSIONS US STANDARD

CODE USA	94066926	RC (IN)	253.9
SW (IN)	29.9	RIM REC	DW 25 B
OD (IN)	85.6	RIM ALT	DW 24 B
SLR (IN)	37.7	ECE	E11-106R-006765

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	9530	11060	12590	14300	15830	17350	19060
FROM 40 TO 25	10470	12150	13820	15710	17380	19060	20940
20	10680	12400	14110	16030	17740	19440	21360
12	10890	12640	14380	16340	18090	19830	21780
5	11520	13370	15210	17280	19120	20960	23040
*UPTO 5 CYC WITH FRONT LOADER	14660	17010	19360	21990	24340	26690	29320
5 HT	10680	12400	14110	16030	17740	19440	21360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.