

AGRIMAX RT 657

TIRE SIZE	600/65 R 34
UM	US STANDARD
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	157 D ; 160 A8



DIMENSIONI US STANDARD

CODICE USA	94032327	RIM REC	DW 20 B
SW (IN)	24.1	RIM ALT	W 18 L
OD (IN)	64.7	ECE	E4-106R-001405
SLR (IN)	29.2	TRA CODE	R1W
RC (IN)	195.3	TREAD DEPTH (32nd)	68.67

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4360	5090	5730	6370	7010	7550	8370	9100
30	4600	5360	6030	6690	7360	7940	8800	9560
25	4760	5560	6250	6940	7640	8230	9130	9920
20	5030	5860	6590	7330	8060	8690	9630	10460
5 LT	5850	6830	7680	8540	9390	10120	11220	12190
5 HT	5030	5860	6590	7330	8060	8690	9630	10460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.