


# AGRIMAX PROCROP

|              |  |
|--------------|--|
| TIRE SIZE    | VF 320/90 R 46   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | ОПРЫСКИВАТЕЛЬ  |
| VERSION      | STEEL BELTED   |
| TIRE TYPE    | TL   |
| LI/SS        | 165 D  |



## РАЗМЕРЫ US STANDARD

|          |          |         |                  |
|----------|----------|---------|------------------|
| USA CODE | 94514700 | RC (IN) | 210.4            |
| SW (IN)  | 12.7     | RIM REC | DW11             |
| OD (IN)  | 68.9     | RIM ALT | W11;DW10         |
| SLR (IN) | 32.2     | ECE     | E11-106R-0011308 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 14   | 12   | 20   | 23   | 26   | 29    | 32    | 35    | 38    | 41    | 44    | 47    | 49    | 52    | 55    | 58    | 61    | 64    |
|---------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 4520 | 5050 | 5680 | 6210 | 6520 | 6840  | 7050  | 7260  | 7620  | 8000  | 8300  | 8620  | 8890  | 9150  | 9410  | 9670  | 10090 | 10510 |
| FROM 40 TO 25 | 4890 | 5460 | 6140 | 6710 | 7050 | 7390  | 7620  | 7840  | 8240  | 8640  | 8980  | 9320  | 9610  | 9890  | 10170 | 10450 | 10910 | 11360 |
| 20            | 4990 | 5570 | 6270 | 6850 | 7190 | 7540  | 7780  | 8010  | 8400  | 8810  | 9160  | 9510  | 9800  | 10090 | 10380 | 10660 | 11130 | 11590 |
| 12            | 5090 | 5680 | 6390 | 6980 | 7330 | 7690  | 7930  | 8160  | 8580  | 8990  | 9340  | 9700  | 9990  | 10290 | 10590 | 10880 | 11360 | 11820 |
| 5*            | 5380 | 6000 | 6750 | 7380 | 7750 | 8130  | 8380  | 8620  | 9070  | 9510  | 9880  | 10260 | 10560 | 10870 | 11190 | 11500 | 12000 | 12490 |
| UPTO 10 CYC.  | 6630 | 7400 | 8320 | 9090 | 9550 | 10010 | 10320 | 10630 | 11170 | 11700 | 12160 | 12630 | 13010 | 13400 | 13780 | 14170 | 14790 | 15390 |
| UPTO 20 CYC.  | 5560 | 6200 | 6970 | 7620 | 8010 | 8390  | 8650  | 8910  | 9360  | 9820  | 10200 | 10590 | 10910 | 11230 | 11560 | 11880 | 12390 | 12900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.