


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>480/80 R 30 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	162 A8 ; 157 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94033850	<b>RC (IN)</b>	180.2
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	60.2	<b>RIM ALT</b>	W 16 L
<b>SLR (IN)</b>	27.0	<b>ECE</b>	E4-106R-002298

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	4280	5280	6180	7190	8090	9090
30	4640	5730	6710	7800	8780	9880
25	4930	6070	7120	8280	9330	10470
20	5110	6320	7410	8610	9690	10890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.