


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	163 D



DIMENSIONES US STANDARD

CÓDIGO USA	94070930	RC (IN)	175.3
SW (IN)	23.5	RIM REC	DW 21 B
OD (IN)	58.7	RIM ALT	DW 20 B
SLR (IN)	25.8	ECE	E11-106R-007602

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	4990	5780	6560	7440	8130	8820	9790
FROM 40 TO 25	5490	6350	7210	8170	8930	9680	10750
20	5600	6480	7350	8340	9100	9880	10970
12	5710	6600	7500	8500	9280	10060	11180
5	6040	6990	7930	8990	9820	10650	11830
*UPTO 5 CYC WITH FRONT LOADER	7680	8880	10090	11440	12490	13550	15050
5 HT	5600	6480	7350	8340	9100	9880	10970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.