


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 900/50 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	881	<b>RIM REC</b>	DW 30 B
<b>OD (MM)</b>	1955	<b>RIM ALT</b>	TW 30 B
<b>SLR (MM)</b>	872	<b>ECE</b>	E11-106R-006492
<b>RC (MM)</b>	5830	<b>SRI</b>	950

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3345	3855	4440	4950	5530	6040	6770	7280
<b>FROM 65 TO 40</b>	3680	4240	4880	5440	6080	6640	7440	8000
30	3825	4405	5075	5655	6320	6905	7735	8320
20	3970	4575	5270	5875	6565	7170	8035	8640
10	4670	5380	6195	6905	7720	8430	9445	10160
<b>UPTO 30 CYC</b>	4780	5510	6340	7070	7900	8630	9670	10400
<b>UPTO 15 CYC</b>	5700	6570	7560	8430	9420	10290	11530	12400
<b>UPTO 10 CYC</b>	6255	7205	8295	9245	10335	11285	12645	13600
10HT	3825	4405	5075	5655	6320	6905	7735	8320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.