DATA SHEET

Última atualização
2-06-2026

AGRIMAX TERIS

TIRE SIZE	**1050/50 R 32 CHO**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CEIFEIRA / COLHEDORA DE ALGODÃO
VERSÃO	HD
TIRE TYPE	TL
LI/SS	184 A8 ; 181 B

DIMENSÕES IS STANDARD

SW (MM)	1059	**RIM REC**	36.0 VA (multipiece)
OD (MM)	1893	**ECE**	E11-106R-0010258
SLR (MM)	840	**SRI**	875
RC (MM)	5685		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3715	4210	5280	5860	6520	7015	7675	8250
40	4050	4590	5760	6390	7110	7650	8370	9000
30	4335	4915	6165	6840	7610	8190	8960	9630
15 CYC	6685	7575	9505	10545	11735	12625	13815	14850
10 CYC	7290	8265	10370	11505	12800	13770	15070	16200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..