


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/75 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 111 A8 |
| LI/SS FREE ROLLING | 123 A8 |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94018567 | RC (IN) | 94.6 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 30.9 | ECE | E4-106R-001812 |
| SLR (IN) | 14.2 | PR | 10 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 57 |
|-----------|------|
| 5 FR | 4780 |
| 15 FR | 4070 |
| 20 FR | 3820 |
| 25 FR | 3420 |
| 5 DW | 3360 |
| 15 DW | 2850 |
| 20 DW | 2690 |
| 25 DW | 2400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.