

MULTIMAX MP 522

TIRE SIZE	540/70 R 24 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	168 A8/B



DIMENSIONS US STANDARD

USA CODE	94052264	RC (IN)	162.7
SW (IN)	20.9	RIM REC	DW 16 L
OD (IN)	53.8	RIM ALT	DW 18 L
SLR (IN)	24.1	ECE	E11-106R-002967

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	5930	7040	8020	9140	10250	10990	12350	-	-
25	5930	7040	8020	9140	10250	10990	12350	-	-
20	6350	7540	8600	9790	10980	11770	13220	-	-
15	6590	7830	8920	10150	11390	12210	13710	-	-
5 CYC.	7230	8900	10470	12040	13710	14910	16850	17780	18520
STATIC	11080	13630	16050	18460	21020	22860	25850	27260	28390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.