


# AGRIMAX FORCE

IF 650/60 R 34

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	165 D



## UNDEFINED IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1644	RIM ALT	DW 21 B
SLR (MM)	746	ECE	E11-106R-006014
RC (MM)	4954	SRI	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2150	2475	2855	3185	3555	3885	4350	4685
FROM 65 TO 40	2365	2725	3140	3500	3910	4270	4785	5150
30	2455	2830	3265	3640	4065	4440	4975	5355
20	2550	2940	3390	3780	4220	4610	5165	5560
10	3000	3460	3985	4445	4965	5420	6075	6540
*UPTO 10 CYC WITH FRONT LOADER	3310	3815	4395	4900	5470	5975	6695	7210
10 HT	2455	2830	3265	3640	4065	4440	4975	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.