


# FL 630 ULTRA

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/50 R 22.5</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPREADER / TANKER / TRAILER /<br>IMPLEMENTS  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 159 D ; 170 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 611  | <b>RIM REC</b> | AG 20.00        |
| <b>OD (MM)</b>  | 1172 | <b>ECE</b>     | E11-106R-003960 |
| <b>SLR (MM)</b> | 518  | <b>SRI</b>     | 550             |
| <b>RC (MM)</b>  | 3533 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1280 | 1480 | 1675 | 2020 | 2355 | 2680 | 3020 | 3330 | 3670 | 3985 |
| 65         | 1400 | 1620 | 1840 | 2220 | 2585 | 2950 | 3310 | 3660 | 4025 | 4375 |
| 50         | 1695 | 1960 | 2225 | 2700 | 3125 | 3575 | 4000 | 4420 | 4875 | 5295 |
| 40         | 1920 | 2220 | 2520 | 3040 | 3540 | 4050 | 4555 | 5020 | 5520 | 6000 |
| 25         | 2215 | 2560 | 2905 | 3510 | 4080 | 4675 | 5210 | 5800 | 6365 | 6915 |
| 10         | 2520 | 2915 | 3310 | 4000 | 4650 | 5325 | 5940 | 6600 | 7245 | 7875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.