


AGRIMAX RT 945

| | |
|---------------------|--|
| TYRE SIZE | 380/90 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 159 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 380 | RIM REC | W 12 |
| OD (MM) | 1852 | RIM ALT | W 11 ; W 13 |
| SLR (MM) | 859 | ECE | E4-106R-001409 |
| RC (MM) | 5699 | SRI | 875 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1785 | 2290 | 2790 | 3065 | 3295 | 3605 | 3875 | 4070 | 4375 | - |
| 40 | 1785 | 2290 | 2790 | 3065 | 3295 | 3605 | 3875 | 4070 | 4375 | - |
| 30 | 1910 | 2450 | 2990 | 3280 | 3530 | 3860 | 4150 | 4360 | 4685 | - |
| 10 | 2095 | 2735 | 3315 | 3955 | 4540 | 4715 | 5235 | 5815 | 6040 | 6565 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.