


# AGRIMAX FORCE

**IF 650/75 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	175 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94069477	<b>RC (IN)</b>	228.4
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	76.4	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	34.1	<b>ECE</b>	E11-106R-007385

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6520	7490	8590	9700	10810	11920	13020	13850
<b>FROM 40 TO 25</b>	7160	8230	9440	10650	11880	13090	14310	15220
20	7450	8560	9830	11090	12360	13620	14890	15830
12	7730	8890	10200	11510	12820	14150	15460	16440
5	9090	10440	11990	13540	15080	16630	18170	19330
<b>UPTO 20 CYC</b>	9310	10690	12270	13850	15440	17010	18600	19780
<b>UPTO 10 CYC</b>	11090	12750	14630	16520	18400	20290	22170	23580
<b>UPTO 5 CYC</b>	12160	13970	16040	18110	20180	22250	24320	25860
5 HT	7450	8560	9830	11090	12360	13620	14890	15830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.