

# PL 801

<b>TIRE SIZE</b>	<b>5.00 - 8</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / КОМБАЙН / ВИЛОЧНЫЙ ПОГРУЗЧИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94032259	<b>RIM ALT</b>	3.25 I
<b>SW (IN)</b>	5.3	<b>PR</b>	10
<b>OD (IN)</b>	18.4		
<b>RIM REC</b>	3.00 D		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	145
15 LOAD WHEEL	3120
15 STEER WHEEL	2405
5 OTHER VEHICLES	3120
15 OTHER VEHICLES	2405
STATIC SIDE LOADER	3625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.