


# EARTHMAX SR 22

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>20.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL                     |
| <b>MACHINERY</b>    | MOTONIVELADORA / CARREGADORA /<br>TRATOR DE ESTEIRA / CARREGADORA<br>/ TRATOR DE ESTEIRA /<br>MOTONIVELADORA |
| <b>VERSÃO</b>       | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 177 B ; 193 A2   |



## DIMENSÕES US STANDARD

|                   |          |                    |           |
|-------------------|----------|--------------------|-----------|
| <b>CÓDIGO USA</b> | 94052431 | <b>RIM REC</b>     | 17.00/2.0 |
| <b>OD (IN)</b>    | 58.7     | <b>RIM ALT</b>     | 17.00/1.7 |
| <b>SLR (IN)</b>   | 25.2     | <b>TRA CODE</b>    | E2/L2     |
| <b>RC (IN)</b>    | 169.9    | <b>STAR RATING</b> | ★★        |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    | 73    | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 12800 | 13600 | 14300 | 14800 | 15200 | 16100 | -     | -     | -     | -     | -     |
| 5         | -     | -     | -     | -     | -     | 21500 | 22000 | 22700 | 24000 | 24700 | 25400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.