

# AGRIMAX SPARGO

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | <b>VF 380/105 R 50</b> |
| <b>UM</b>           | IS STANDARD            |
| <b>CONSTRUCTION</b> |                        |
| <b>MACHINERY</b>    | TRACTOR                |
| <b>VERSION</b>      | STANDARD               |
| <b>TIRE TYPE</b>    | TL                     |
| <b>LI/SS</b>        | 179 D                  |



## DIMENSIONS IS STANDARD

|                 |      |                |                             |
|-----------------|------|----------------|-----------------------------|
| <b>SW (MM)</b>  | 400  | <b>RIM REC</b> | W 13 A                      |
| <b>OD (MM)</b>  | 2050 | <b>RIM ALT</b> | W 12; DW 12; DW 13; DW 13 L |
| <b>SLR (MM)</b> | 934  | <b>ECE</b>     | E4-106R-002397              |
| <b>RC (MM)</b>  | 6211 | <b>SRI</b>     | 975                         |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6  | 3.8  | 4.0  | 4.2  | 4.4  |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70            | 3380 | 3805 | 4155 | 4370 | 4580 | 4720 | 4860 | 5145 | 5355 | 5565 | 5780 | 5990 | 6130 | 6345 | 6485 | 6765 | 7050 |
| FROM 65 TO 40 | 3720 | 4185 | 4570 | 4805 | 5035 | 5190 | 5345 | 5655 | 5890 | 6120 | 6355 | 6585 | 6740 | 6975 | 7130 | 7440 | 7550 |
| 30            | 3790 | 4265 | 4660 | 4990 | 5135 | 5295 | 5450 | 5770 | 6005 | 6240 | 6480 | 6715 | 6875 | 7110 | 7270 | 7585 | 7905 |
| 20            | 3865 | 4350 | 4755 | 4995 | 5235 | 5400 | 5560 | 5880 | 6125 | 6365 | 6605 | 6850 | 7010 | 7250 | 7415 | 7735 | 8060 |
| 10            | 4090 | 4600 | 5025 | 5285 | 5540 | 5710 | 5880 | 6220 | 6475 | 6730 | 6990 | 7245 | 7415 | 7670 | 7840 | 8180 | 8525 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.