

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	145 A8/142 B
<b>LI/SS FREE ROLLING</b>	157 A8/154 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	515	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1181	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (MM)</b>	542	<b>ECE</b>	E4-106R-002314
<b>RC (MM)</b>	3604	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	2.00	2.40
10 FR	4390	5195	5775
20 FR	3950	4675	5200
30 FR	3510	4155	4620
40 FR	3135	3710	4125
50 FR	2820	3340	3750
10 DW	3085	3645	4060
20 DW	2780	3280	3655
30 DW	2470	2920	3250
40 DW	2205	2605	2900
50 DW	1985	2345	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.