

# AGRIMAX RT 657

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 440/65 R 28                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | SKÖRDEMASKIN FÖR VINGÅRD /<br>TRAKTOR / SKÖRDEMASKIN                                     |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 138 D ; 141 A8                                                                           |



## DIMENSIONER US STANDARD

|          |          |         |                |
|----------|----------|---------|----------------|
| USA CODE | 94029143 | RC (IN) | 154.6          |
| SW (IN)  | 17.4     | RIM REC | W 14 L         |
| OD (IN)  | 50.5     | RIM ALT | W 13; W 15 L   |
| SLR (IN) | 23.2     | ECE     | E4-106R-000767 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 40        | 2500 | 2920 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| 30        | 2630 | 3060 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| 25        | 2730 | 3190 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| 20        | 2880 | 3360 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| 5 LT      | 3350 | 3910 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| 5 HT      | 2880 | 3360 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.