


# MULTIMAX MP 522



<b>TIRE SIZE</b>	<b>400/70 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 A8/B

## DIMENSIONS US STANDARD

<b>CODE USA</b>	94051403	<b>RC (IN)</b>	138.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	13
<b>OD (IN)</b>	46.1	<b>RIM ALT</b>	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L
<b>SLR (IN)</b>	21.0	<b>ECE</b>	E11-106R-002964

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
<b>30</b>	3760	4460	5090	5800	6500	6970	7830	-	-
<b>25</b>	3760	4460	5090	5800	6500	6970	7830	-	-
<b>20</b>	4020	4780	5450	6210	6960	7460	8380	-	-
<b>15</b>	4180	4960	5650	6440	7220	7750	8700	-	-
<b>5 CYC.</b>	4590	5640	6640	7640	8700	9460	10690	11280	11740
<b>STATIC</b>	7020	8640	10170	11710	13330	14490	16390	17280	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.