

# AS 504

<b>TIRE SIZE</b>	<b>400/50 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	109 A8
<b>LI/SS FREE ROLLING</b>	121 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	395	<b>RIM REC</b>	13 LB
<b>OD (MM)</b>	790	<b>ECE</b>	E11-106R-005494
<b>SLR (MM)</b>	369		
<b>RC (MM)</b>	2387		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00
10 FR	2030
25 FR	1725
30 FR	1625
40 FR	1450
10 DW	1440
25 DW	1225
30 DW	1155
40 DW	1030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.