


# AGRIMAX V-FLECTO



TIRE SIZE	VF 650/75 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOTORSTARK TRAKTOR / TRAKTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	180 D

## DIMENSIONER US STANDARD

USA CODE	94514427	RC (IN)	241.9
SW (IN)	26.8	RIM REC	DW 23 B
OD (IN)	80.9	RIM ALT	DW 21 B
SLR (IN)	35.2	ECE	E11-106R-0011304

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	14	17	20	23	29
45	8020	9300	10580	12040	13320	14590	16050
FROM 40 TO 25	8820	10230	11640	13230	14640	16050	17640
20	8990	10430	11870	13490	14920	16370	17990
12	9170	10640	12100	13760	15220	16690	18340
5	9700	11240	12800	14550	16090	17650	19400
UPTO 20 CYC	10010	11610	13200	15010	16610	18210	20020
UPTO 10 CYC	11950	13860	15760	17920	19830	21740	23900
UPTO 5CYC	13090	15190	17280	19640	21740	23830	26190
5 HT	8990	10430	11870	13490	14920	16370	17990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.