

# IT 400

|                     |                            |
|---------------------|----------------------------|
| <b>TIRE SIZE</b>    | <b>10.00 - 15</b>          |
| <b>UM</b>           | US STANDARD                |
| <b>CONSTRUCTION</b> | ⊠ BIAS                     |
| <b>MACHINERY</b>    | REMORCĂ CU PLATFORMĂ JOASĂ |
| <b>VERSION</b>      | STANDARD                   |
| <b>TIRE TYPE</b>    | TT                         |
| <b>LI/SS</b>        | 143/138 J                  |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94008261 | <b>RC (IN)</b> | 108.1           |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | 7.5             |
| <b>OD (IN)</b>  | 36.4     | <b>RIM ALT</b> | 7.0; 8.0        |
| <b>SLR (IN)</b> | 16.1     | <b>ECE</b>     | E11-54R-0019537 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 140  | 130  | 115  |
|-----------|------|------|------|
| 10        | 9940 | -    | -    |
| 20        | -    | 8020 | -    |
| 62 LS     | -    | 6060 | -    |
| 62 LD     | -    | -    | 5310 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.