

# AGRIMAXFACTOR

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>620/70 R 38</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRAKTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 170 D ; 173 A8     |



## DIMENSIONER US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94076444 | <b>RC (IN)</b> | 219.7            |
| <b>SW (IN)</b>  | 24.6     | <b>RIM REC</b> | DW 20 B          |
| <b>OD (IN)</b>  | 72.2     | <b>RIM ALT</b> | DW 18 L ; W 18 L |
| <b>SLR (IN)</b> | 33.2     | <b>ECE</b>     | E11-106R-0010338 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15    | 17    | 20    | 23    | 29    | 35    | 41    | 47    |
|-------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>40</b>   | 5590 | 6590 | 7590  | 8450  | 9460  | 10320 | 11320 | 12180 | 12300 | 13230 |
| <b>30</b>   | 5870 | 6920 | 7980  | 8880  | 9930  | 10840 | 11890 | 12800 | 12920 | 13890 |
| <b>25</b>   | 6130 | 7230 | 8320  | 9270  | 10360 | 11310 | 12400 | 13350 | 13480 | 14480 |
| <b>15</b>   | 6440 | 7580 | 8740  | 9730  | 10880 | 11870 | 13030 | 14010 | 14150 | 15210 |
| <b>5 LT</b> | 7500 | 8840 | 10180 | 11330 | 12680 | 13830 | 15180 | 16320 | 16490 | 17720 |
| <b>5 HT</b> | 6440 | 7580 | 8740  | 9730  | 10880 | 11870 | 13030 | 14010 | 14150 | 15210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.