


# EARTHMAX SR 41

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>875/65 R 29</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / LOADER / ARTICULATED<br>DUMP TRUCK   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 214 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |                      |
|-----------------|----------|--------------------|----------------------|
| <b>USA CODE</b> | 94059935 | <b>RIM REC</b>     | 27.00/3.50           |
| <b>OD (IN)</b>  | 73.4     | <b>RIM ALT</b>     | 27.00/3.0; 28.00/3.5 |
| <b>SLR (IN)</b> | 33.0     | <b>TRA CODE</b>    | L4                   |
| <b>RC (IN)</b>  | 223.6    | <b>STAR RATING</b> | ★                    |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 5         | 40800 | 43000 | 45400 | 46700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.