DATA SHEET

PRINTED ON
23-04-2026

FLOTATION 648

TIRE SIZE	**650/65 - 30.5**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	167 A8/163 B
LI/SS FREE ROLLING	179 A8/175 B

DIMENSIUNI IS STANDARD

SW (MM)	670	**RIM REC**	AG 20.00
OD (MM)	1660	**ECE**	E4-106R-001550
SLR (MM)	710	**PR**	16
RC (MM)	4935		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	9645	10260	10850
20 FR	8680	9235	9765
30 FR	7715	8210	8680
40 FR	6890	7330	7750
50 FR	6200	6595	6900
10 DW	6785	7215	7630
20 DW	6105	6495	6865
30 DW	5425	5775	6105
40 DW	4845	5155	5450
50 DW	4360	4640	4875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..