

AS 504

TIRE SIZE	10.0/75 - 15.3
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	118 A8
LI/SS FREE ROLLING	130 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	264	RIM REC	9.00
OD (MM)	785	ECE	E4-106R-001545
SLR (MM)	360	PR	14
RC (MM)	2404	SRI	360

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50
10 FR	2660
25 FR	2260
30 FR	2130
40 FR	1900
10 DW	1850
25 DW	1570
30 DW	1480
40 DW	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.