


FLOTATION 648

TIRE SIZE	600/55 - 22.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8/ 148 B
LI/SS FREE ROLLING	164 A8/160 B



DIMENSIONS US STANDARD

CODE USA	94006410	RC (IN)	146.3
SW (IN)	23.6	RIM REC	AG 20.00
OD (IN)	48.4	ECE	E11-106R-004553
SLR (IN)	21.3	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	25	29
5 FR	13040	14030	15430
10 FR	11740	12620	13890
20 FR	10430	11220	12350
25 FR	9310	10020	11020
30 FR	8390	9020	9920
5 DW	8990	9680	10650
10 DW	8100	8710	9580
20 DW	7200	7740	8520
25 DW	6430	6910	7610
30 DW	5790	6220	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.