


AGRIMAX RT 855

TIRE SIZE	520/85 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94057993	RC (IN)	254.8
SW (IN)	20.3	RIM REC	DW 16L
OD (IN)	84.8	RIM ALT	DW 18 L
SLR (IN)	39.1	ECE	E11-106R-004895

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	5350	6140	7045	7950	8865	9770	10685	11355
25	5350	6140	7045	7950	8865	9770	10685	11355
20	5725	6570	7540	8525	9495	10465	11435	12160
5 LT	7165	8225	9450	10660	11885	13095	14320	15225
5 HT	5725	6570	7540	8525	9495	10465	11435	12160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.