


AGRIMAX V-FLECTO



TIRE SIZE	VF 580/85 R 46 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	179 D

РАЗМЕРЫ US STANDARD

USA CODE	94516148	RC (IN)	254.0
SW (IN)	23.8	RIM REC	DW 20 B
OD (IN)	84.9	RIM ALT	DW 21 B, DW18L
SLR (IN)	37.3	ECE	E11-106R-0011691

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	7780	9030	10270	11670	12920	14160	15550
FROM 40 TO 25	8540	9910	11280	12820	14190	15550	17080
20	8720	10110	11510	13070	14470	15860	17430
12	8880	10310	11730	13330	14750	16170	17770
5	9400	10900	12410	14100	15610	17110	18790
5 HT	8720	10110	11510	13070	14470	15860	17430
UPTO 5 CYC	12690	14730	16750	19040	21060	23090	25370
UPTO 10 CYC	11580	13440	15290	17370	19220	21080	23160
UPTO 20 CYC	9700	11250	12810	14550	16100	17660	19400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.