


# AT 171

<b>TIRE SIZE</b>	<b>37X9 - 22</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	88 A8 ; 64 F



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94055203	<b>RC (IN)</b>	109.4
<b>SW (IN)</b>	8.1	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	37.2	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	17.5	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	20	15
25 MUD BOGGING	1235	-
50 MUD BOGGING	617	-
25 CASUAL TRANSPORT	-	1005
50 CASUL TRANSPORT	-	505

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.